

HELICAL PILES

MODEL P1

Shaft

Wall Thickness	0.145" (3.68 mm)
Round HSS Outside Diameter	1.9" (48.3 mm)
Available Standard Lengths	5'-3" (1.6 m) / 7'-0" (2.1 m) / 10'-6" (3.2 m)

Load Specifications

Max. Allowable Capacity*	6.7 kips (29.8 kN)
--------------------------	--------------------

* Higher load ratings could be considered with site-specific engineering.



Technical Specifications

Commonly Used Structure	Light Residential
Code Evaluation	Listed per CCMC 13059-R
Standard Steel	ASTM A500 Grade C Fy=51 ksi min (350 MPa)
Black Steel Design Life	min. 50 years per CCMC 13059-R
Coating	Galvanized or Black Steel
Galvanization Compliance	ASTM A123/A123M
Additional Corrosion Protection	Cathodic Protection System available

Helix

Pitch	3" (76.2 mm)
Thickness	0.375" (9.5 mm)
Standard Steel	CSA G40.21-44W Fy=44 ksi min (300 MPa)
Coating	Galvanized or Black Steel
Multiple Welded Helix	Available
Helix Size*	6" (152 mm) to 12" (305 mm)

* Other sizes available upon request.




HELICAL PILES

MODEL P1

Helical Piles

Sleeve (Available)

Function Utility	Protection against soil movements
Wall Thickness	1/16" (1.6 mm)
Outside Diameter	± 2.125" (± 54.2 mm)
Length	± 66" (± 1.67 m)
Weight	± 0.65 lb (± 0.30 kg)
Material	HDPE
Color	Green



Pile Caps

Wood Structure Connectors

Pages 32, 34, 36, 38, 39, 41, 43