

HELICAL PILES

MODEL P2.5

Shaft

Wall Thickness	0.203" (5.16 mm)
Round HSS Outside Diameter	2.875" (73.0 mm)
Available Standard Lengths	5'-3" (1.6 m) / 7'-0" (2.1 m) / 10'-6" (3.2 m)

Load Specifications

Max. Allowable Capacity*	20 kips (kN)
--------------------------	--------------

* Higher load ratings could be considered with site-specific engineering.



Technical Specifications

Commonly Used Structure	Medium Residential Light Commercial
Standard Steel	ASTM A500 Grade C Fy=51 ksi min (350 MPa)
Black Steel Design Life	min. 50 years
Coating	Galvanized or Black Steel
Galvanization Compliance	ASTM A123/A123M
Additional Corrosion Protection	Cathodic Protection System available

Helix

Pitch	3" (76.2 mm) / 5" (127 mm)
Thickness	0.375" (9.5 mm)
Standard Steel	CSA G40.21-44W Fy=44 ksi min (300 MPa)
Coating	Galvanized or Black Steel
Multiple Welded Helix	Available
Helix Size*	8" (203 mm) to 24" (610 mm)

* Other sizes available upon request.



HELICAL PILES


MODEL P2.5




Helical Piles

Sleeve (Available)

Function Utility	Protection against soil movements
Wall Thickness	1/16" (1.6 mm)
Outside Diameter	± 3.125" (± 79.4 mm)
Length	± 66" (± 1.67 m)
Weight	± 1.25 lb (± 0.57 kg)
Material	HDPE
Color	Green



Outside Couplings



Regular	
Assembly	Welded
Wall Thickness	0.216" (5.49 mm)
Round HSS Outside Diameter	3.5" (88.9 mm)
Standard Steel	ASTM A500 Grade C Fy=51 ksi min (350 MPa)
Length*	3.5" (88.9 mm)

* Factory welded or welded on site.

Pile Caps

Wood Structure Connectors	Pages 33, 40, 42, 44, 45, 47, 48
Steel Structure Connectors	Page 46
Concrete Construction Connectors	Pages 46, 49-51