

WOOD STRUCTURE CONNECTORS

U PLATE - FIXED

A1/2-FIX + PUE-4 OR PUE-5

Application

Used for connecting wood post and beams.

Mechanical Capacity


Single bearing plate

Ultimate Compression / Tension	22 kips / 4 kips
Allowable Compression / Tension	11 kips / 2 kips


Technical Specifications

Material (standard) :

Cap	CSA G40.21 / 300W
Adapter	Casted 1018 steel
Threaded rod	1" Ø SAE Grade 2
Button head cap screw	3/8" Ø - Grade 5
Socket head set screws	3/8" Ø - Grade 5
Black Steel Design Life	50 years per AC358
Coating	Galvanized
Galvanization compliance	ASTM A123



A1/2-FIX + PUE-5 Simple



Geometry :

Pile Model	Model No.	Dimensions			
		Length	Width	Height	Thickness
P1, P2 or P2HD	A1/2-FIX + PUE-4	4" (101.6 mm)	3.5625" (90.5 mm)	2.75" (69.9 mm)	0.25" (6.4 mm)
	A1/2-FIX + PUE-5	4" (101.6 mm)	5.5625" (141.3 mm)	4" (101.6 mm)	0.25" (6.4 mm)

WOOD STRUCTURE CONNECTORS

U PLATE - FIXED

A1/2-FIX + PUE-4 OR PUE-5

Allowable capacity for common applications :

Pile Model	Model No.	Supported member	Allowable Capacity			
			Compression (Down)	Tension (Uplift)		Lateral
				3/8" lag screws	#8 screws	
P1, P2 or P2HD	A1/2-FIX + PUE-4	2 ply 2 x ___ SPF Beam	4,000 lb (17,8 kN)	1,025 lb (4.6 kN)	700 lb (3.1 kN)	700 lb (3.1 kN)
		2 ply - LVL beam	9,000 lb (40,0 kN)	1,750 lb (7.8 kN)		
		4 x 4 SPF Post	9,000 lb (40,0 kN)	1,625 lb (7.2 kN)		
	A1/2-FIX+ PUE-5	3 ply 2 x ___ SPF Beam	5,000 lb (23,6 kN)	1,025 lb (4.6 kN)	700 lb (3.1 kN)	700 lb (3.1 kN)
		3 ply - LVL beam	11,000 lb (48,9 kN)	1,750 lb (7.8 kN)		
		6 x 6 SPF Post	11,000 lb (48,9 kN)	1,625 lb (7.2 kN)		

Pile Caps

Installation instructions and special notes

1. Allowable tension and lateral capacity are based on NDS code and load duration Cd=1.6
2. Allowable compression capacity are based on NDS code and internal testing. Cap must directly bear on shaft below.
3. For wet use multiply table values by 0.7
4. Use all specified fasteners (or approved equivalent) lag screws 3/8" Ø x 2" long or wood screws #8 x 2" long
5. Uplift connection from cap to shaft shall be to apply minimum of 15 ft-lb torque of set screws.
6. Capacity above 7,000 lb must be limited to 1/4" misalignment. For capacity below 7,000 lb, pile installation tolerances must be within 1/2" of misalignment and ± 1° of inclination.
7. Structural Designer is responsible for wood design and verifying capacity of connection to wood members
8. Loads shall be reduced where limited by capacity of the wood and/or capacity of the installed pile
9. For any questions regarding uplift, lateral and compression capacities please contact TMP Engineers at eng.usa@technometalpost.com